

PRODUCT IDENTIFICATION

A-1 Grit White Marble Roofing Aggregate

WEST COAST
#1711WMW80
- 80 lb bag
1711WMW3000
- 3000 lb super sack

A HIGHLY REFLECTIVE AGGREGATE FOR USE IN THE SOLARGARD G ADHESIVE ROOF SURFACING SYSTEM

Composition

A-1 Grit White Marble Roofing Aggregate is a white, highly reflective, kiln dried, durable roof surfacing material.

Uses

A-1 Grit White Marble Roofing Aggregate is used in conjunction with Republic SOLARGARD G Adhesive to provide a highly reflective, high emissivity roof surfacing system for use in restoration of built up (BUR) and Modified Bitumen (MB) roofing systems. The SOLARGARD G system, featuring A-1 Grit White Marble Roofing Aggregate, is suitable for use as a restoration surfacing on existing roofs that are in good condition.

A roof surface consisting of A-1 Grit White Marble Aggregate adhered in SOLARGARD G Adhesive meets the requirements of California’s Title 24 Energy Efficiency Standards for Non-Residential Buildings and has been tested according to the standards of the Cool Roof Rating Council (CRRC). A roof surface consisting of A-1 Grit White Marble Roofing Aggregate in SOLARGARD G Adhesive could also qualify for a point towards the overall LEED certification of a project. A-1 Grit White Marble Roofing Aggregate must be applied in SOLARGARD G Adhesive in order to obtain this particular rating and classification.

Limitations

Not intended to perform under ponding water conditions. Positive drainage required.

Color: White

Size: 3/8” (#4)

Packaging:

Available in 7/8 cubic foot (0.025m) bags, which is approx. 80 lb.(36.3 kg.) with 35 bags per pallet. Also available in 3000 lb. (1360.7 kg.) super sacks (No deposit, no return bags)

Availability:

A-1 Grit White Marble Roofing Aggregate is supplied/ shipped out of California. The supplier serves the Western half of the United States. There is a 3 week lead time for material delivery.

PRODUCT ADVANTAGES

FEATURES

Highly reflective surface

BENEFITS

- Keeps roof surface temperature lower than typical gravel
- Reduces air conditioning loads during peak day
- Reduces Urban Heat Island Effect
- Improves comfort within building

Durable surfacing

- Long life
- Protection from hail and falling objects
- Resists damage from traffic

Kiln Dried

- Low dust
- Consistently dried

PHYSICAL PERFORMANCE CHARACTERISTICS

PROPERTY

TYPICAL VALUE

- | | |
|-------------------------|------------|
| Hardness | - 5.0 mohs |
| Specific Gravity | - 2.75 |
| Color | - White |



Republic Powdered Metals, Inc.
2628 Pearl Road • Medina, OH 44256
www.rpmrepublic.com

A-1 Grit White Marble Roofing Aggregate

Surface Preparation

All detail and flashing applications must cure at least 1 day prior to the application of SOLARGARD G Adhesive.

Refer to appropriate application specification for further information.

Application

Fully mix the SOLARGARD G Adhesive prior to application. Review the product data or label information for proper mixing instructions. Apply the SOLARGARD G Adhesive to the roof surface at a coverage rate of 7 gal / 100 sq. ft. (min). Immediately broadcast 250 lbs / 100 sq. ft. of new clean A-1 Grit White Marble Roofing Aggregate into the adhesive.

Refer to appropriate application specification for further information.

Maintenance

It is recommended that the coated area be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Recoating or small area touch up can be made at any time by following recommended application procedures.

Technical Services

Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Material Safety Data Sheet (MSDS) for precautionary information.



Republic Powdered Metals, Inc.

2628 Pearl Road • Medina, OH 44256

800/551-7081 • Fax: 800/382-1218 • www.rpmrepublic.com

The information provided on this data sheet is effective as of August 2008 and supersedes all previous data concerning this product and its application.

© Republic Powdered Metals, Inc., 2008. All Rights Reserved.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Republic DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO REPUBLIC'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL REPUBLIC BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, REPUBLIC'S LIABILITY IS LIMITED, AT REPUBLIC'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.